

PRISMA . PRISMA T . PRISMA TT



FAST HEATING

Il design della griglia nella parte superiore amplifica l'effetto convettivo rendendo Prisma un convettore a bassissima inerzia, ideale se si necessita di riscaldare l'ambiente in poco tempo.

The design of the grille in the upper part widens the convection range, making Prisma a very low inertia convector, ideal when a room needs to be heated very quickly.



METAL FRAME

Le forme decise, la leggerezza e la solidità di Prisma sono resi possibili dal telaio e dalla scocca in metallo verniciato.

The clean shape, lightness and solidity of Prisma are made possible by the painted metal frame and shell.



COMPACT TECHNOLOGY

Estrema compattezza nelle forme e soli 17 cm di spessore.

Extremely compact shape and only 17 cm thick.

TERMOCONVETTORI CARATTERISTICHE

3 versioni disponibili
Potenza termica max 2000 W
3 livelli di potenza (800 - 1200 - 2000 W)
Comandi meccanici
Termostato di sicurezza
Installazione a pavimento o a parete
Pratiche Maniglie
Funzione Turbo: ventilazione ausiliaria (solo Prisma T e Prisma TT)
Timer 24 h (solo Prisma TT)
Kit fissaggio a muro incluso
Volume massimo riscaldabile: 60 m³

THERMOCONVECTORS FEATURES

3 different versions
Max thermal output: 2000 W
3 power settings (800 - 1200 - 2000 W)
Mechanical controls
Safety thermostat
Wall or floor installation
Practical Handles
Turbo Function: auxiliary fan (only Prisma T e Prisma TT)
24h Timer (only Prisma T)
Wall mounting kit included
Max room volume: 60 m³